

Eastto Multigrade 10w-30,20w-40, 20w-50

GRADE: 10W-30, 20W-40, 20W-50

INTRODUCTION:

Eastto MULTIGRADE 10W-30, 20W-40, 20W-50 are blended from highly refined base stocks and specially selected additives to meet special characteristics and performance levels, like excellent thermal and oxidation stability, protection against rust, corrosion and wear. They have very high viscosity index to provide ease in starting and ensure adequate oil film thickness at extreme temperature to eliminate seasonal oil changes, reduce oil consumption, and keep the engine clean

APPLICATION:

EASTTO MULTIGRADE 10W-30, 20W-40, 20W-50 oils are recommended for use in gasoline and diesel engines operating over wide range of temperatures throughout the year.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO MULTIGRADE 10W-30	EASTTO MULTIGRADE 20W-40	EASTTO MULTIGRADE 20W-50
Kinematic Viscosity at 100°C, cSt,	12.0	14	18
Flash Point, COC, °C	190	200	200
TBN, mg KOH / gm	6.0	6.0	6.0
Pour Point, °C, Max.	(-) 24	(-) 21	(-) 21

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Multigrade 10w-30, 20w-40, 20w-50