

PRODUCT DATASHEET

PRODUCT: EASTTO 2T OIL

GRADE: TWO STROKE ENGINE OIL

INTRODUCTION: EASTTO 2T OIL is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of two stroke engines manufactured by all leading auto makers. It is blended from selected base stocks and special additives to minimise spark plug fouling and pre-ignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It is specifically formulated to give additional advantage of lower consumption of fuel. It contains a diluent for easy mixing with gasoline and is dyed green for easy identification.

APPLICATION: EASTTO 2T OIL is recommended for lubrication of Mopeds, Scooters, Motorcycles and Auto rickshaws, operating on two stroke engines. The recommended dosage is 20 ml of oil per litre of petrol or **as per recommendation of OEM.**



Motorcycles and mopeds operating on two stroke engines

Auto rickshaws with two stroke engines

PERFORMANCE LEVEL: EASTTO 2T OIL meets the performance level of JASO FC specifications.

TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHODS	EASTTO 2T OIL
Kinematic Viscosity at 40°C, cst	ASTM D 445	55
Flash Point, COC, °C	ASTM D 92	200
Sulphated Ash, % by Weight, Max.	ASTM D 874	0.25
Pour Point, °C	ASTM D 97	-12

PACKING: 500 ml bottle, 1 liter, 5 liters, 20 liters, 50 liters, 210 liters

Date of issue: 04.09.2014

Date of revision: 05.03.2019

1st Revision: 29.05.2019 (CK)

PDS: 01.17.01





Eastern Petroleum Pvt. Ltd.

an ISO 9001-2015 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 25299990

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**
Specification variation in these characteristics may occur.

