



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company
Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, 2529 9990,
Email: office@easternpetroleum.in, Web: www.easternpetroleum.in
CIN NO: U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name : EASTTO GAS ENGINE OILS SAE 40 CD/SF, 20W-50 CD/SF
Product Use : Automotive lubricants
Supplier : Eastern Petroleum Pvt. Ltd
235-239, Jaw ahar industrial Estate, Kamothe, Panvel,
Dist- Raigad, Maharashtra: 410209
Telephone No : 91-22-2743 1694, 91-22-2743 3819.
Email : sales@easternpetroleum.in

2. Composition / Information of Ingredients

Ingredient name	CAS Number	% by wt
Mineral base oil	64742-65-0	90 - 95
Multifunctional additive	Mixture	5 - 10

3. Hazards identification

Non dangerous substance
Physical state : Liquid
Human Health Effects
Eyes : Not expected to cause Eyes irritation
Skin : Not expected to cause skin irritation
Inhalation : Not expected to cause any side effect w hile inhalation

4. First Aid Measures

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact : Immediately wash affected area w ith soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts : In case of contact immediately w ash eyes w ith plenty of w ater.
Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been sw allow ed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flam mability of product : Combustible liquid
Extinguishing Media
Suitable : Use dry chemical, carbon dioxide (CO₂), or foam
Not suitable : Do not use w ater.

6. Accidental Release Measures

Personal precautions : Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Pick up free liquid for recycling or disposal. The residual oil can be transferred to another container.

Clean up method- small spillage Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.

Clean up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

7. Handling and Storage

Handling Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapours or mists might be released and require a well ventilated workplace.

Storage Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. Exposure Controls / Personal Protection

Control parameters Exposure via air and normal handling

Personal protection equipment

Respiratory protection Avoid inhalation use suitable mask with filter if necessary.

Hand protection Wear oil-resistant protective gloves if there is a risk of skin contact.

Eye protection For eyes protection wear safety goggles.

Skin and body protection Use protective cloths and gloves.

Hygienic measures Act in accordance with good industrial Hygiene and safety practice.

9. Physical and Chemical Properties

CHARACTERISTICS	EASTTO GAS ENGINE OIL SAE 40 CD/SF	EASTTO GAS ENGINE OIL SAE 20W-50 CD/SF
Physical state	Liquid	Liquid
Odour	Mild	Mild
Kinematic viscosity @ 100 °C, cst	14	18.5
Solubility in water	Insoluble	Insoluble
pH	N.A	N.A
Flash point °C	220	220

10. Stability and Reactivity

Reactivity and stability Stable at normal conditions and decompose at higher temperature.

Conditions to avoid Excessive heating and highly oxidizing agents

Hazardous decomposition products Hazardous decomposition products are not expected to form during normal storage.

Hazardous polymerization Polymerization will not occur.

11. Toxicological Information

Potential chronic health effects
Carcinogenicity No known significant effects or critical hazards.

12. Ecological Information

Environment effect: Will not have chronic effect on aquatic environment

13. Disposal considerations

Waste disposal procedure: Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.

14. Transport Information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

15. Regulatory Information

Not classified as hazardous.

16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.