

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO PUMP SET OIL SAE 40, 50

**INTRODUCTION:**

**EASTTO PUMP SET OIL SAE 40, 50** are blended from highly refined base stocks with high viscosity index and advanced additives that provides detergent, dispersant, anti-oxidant and anti-wear properties. Besides lowering the maintenance cost, **EASTTO PUMP SET OIL SAE 40, 50** enhance the engine life with less wear and tear.

**APPLICATION:**

**EASTTO PUMP SET OIL SAE 40, 50** are recommended for use as crankcase oils for slow, medium and high speed stationary diesel engines, e.g. as Pump Set Oil, Generator Set Oil etc.



High speed stationary diesel engines.



Pump Set.

**PERFORMANCE LEVEL:**

**EASTTO PUMP SET OIL SAE 40, 50** meet the performance level of API CC/SC, IS: 13656-2014, EPL-1/EDL-1, SAE 40, 50

**TYPICAL PROPERTIES**

CHARACTERISTICS	EASTTO PUMP SET OIL SAE 40	EASTTO PUMP SET OIL SAE 50
Kinematic Viscosity at 100°C, cst	14.0	19.0
Flash Point, °C, Min.	220	220
TBN, mg KOH / gm	5.0	5.0
Pour Point, °C	- 6	- 6

**PACKING:** 210 Litres Drum

**Date of issue:** 08.09.2014

**Date of revision:** 26.08.2016

**1<sup>st</sup> Revision:** 30.05.2019 (CK)

**PDS No.** 01.16.01 – 01.16.02





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: [office@easternpetroleum.in](mailto:office@easternpetroleum.in), Web: [www.easternpetroleum.in](http://www.easternpetroleum.in)

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

