

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO SHOCK ABSORBER OIL 12, 18

**INTRODUCTION:** EASTTO SHOCK ABSORBER OIL 12, 18 are blended from high viscosity index oils and specially selected additives to provide excellent anti-wear, anti-rust and anti-oxidation properties. EASTTO SHOCK ABSORBER OIL 12, 18 have very good chemical stability, excellent seal compatibility and very low pour point characteristics.

**APPLICATION:** EASTTOSHOCK ABSORBER OIL 12, 18 are recommended for use in shock absorbers.



**PERFORMANCE LEVEL:** Proprietary product

### TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SHOCK ABSORBER OIL 12	EASTTO SHOCK ABSORBER OIL 18
Kinematic Viscosity at 40°C, cst	12	18
Viscosity Index, Min.	45	45
Flash Point, COC, °C, Min.	145	160
Pour Point, °C	-39	-36

**PACKING:** 210 Litres Drums.

**Date of issue:** 09.09.2014

**Date of revision:** 26.08.2016

1<sup>st</sup> Revision: 30.05.2019 (CK) **(VI is Very Low .PLZ CONFIRM VISCOSITY INDEX)**

**PDS No.** 01.45.01 – 01.46.02





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990

Email: [office@easternpetroleum.in](mailto:office@easternpetroleum.in), Web: [www.easternpetroleum.in](http://www.easternpetroleum.in)

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

