

PRODUCT DATA SHEET

PRODUCT:	EASTTO AXLE OILS
GRADE:	60 (Light), 80 (Medium), 100 (Heavy)
INTRODUCTION:	These oils are blended from refined base stocks having good thermal and oxidation stability with required load bearing and antiwear additives.
APPLICATION:	These oils are recommended for use in plain bearings and axle boxes of locomotives and wagons required by Railways and Steel Plants.



This oil is recommended for use in plain bearings

PERFORMANCE LEVEL:	Meets IS: 1628 – 1986 (Reaffirmed 2002) Specification.
---------------------------	--

TYPICAL PROPERTIES:

TYPICAL PROPERTIES	EASTTO AXLE OILS		
	60 (LIGHT)	80 (MEDIUM)	100 (HEAVY)
Kinematic Viscosity at 60° C, cSt	60	80	100
Viscosity Index	40	40	40
Flash Point, (PMCC) ° C	160	160	180
Pour Point, °C	-3	-3	-3

PACKING: 210 Litres Drums

Date of Issue : 13.09.2014

Date of Revision: 06.08.2016

PDS No. 03.51.01 – 03.51.03

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

