

PRODUCT DATA SHEET

PRODUCT: EASTTO HYDRAULIC OILS AW

GRADE: ISO VG 32, 46, 57, 68, 81, 100, 150

INTRODUCTION: EASTTO HYDRAULIC OILS AW are blended from highly refined base stocks and specially selected Anti-oxidant, Anti-corrosion, Anti-wear and Anti-foam additives. These oils can sustain very high pressure of the system and high speed of the pumps and compatible with the seals normally used in the hydraulic system.

APPLICATION: EASTTO HYDRAULIC OILS AW is designed for use in Mobile and Stationary hydraulic Vane, Piston and Gear type pumps. It is recommended for moderate hydraulic systems and wide variety of circulating systems of industrial equipments. These oils are also recommended for Circulation, Splash, Ring oiling systems of the Bearings and Gears of industrial machinery that require a long life lubricant. These oils can also be used for chain drives and compressor crankcase lubrication.



PERFORMANCE LEVEL: IS: 10522:1983 [Reaffirmed 2004]

TYPICAL PROPERTIES

EASTTO HYDRAULIC OILS AW							
Characteristics	32	46	57	68	81	100	150
Kinematic viscosity @ 40°C	32	46	57	68	81	100	150
Viscosity Index	95	95	95	95	95	95	95
Flash Point (COC), °C	190	210	210	210	210	220	220
Pour Point, °C	-6	-6	-6	-6	-6	-6	-6

PACKING: 210 Litres Drums.

Date of issue : 13.09.2014

Date of Revision: 06.08.2016

1st Revision: 29.05.2019 (CK)

PDS No. 03.03.01 - 03.03.07





Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**
Specification variation in these characteristics may occur.

