

Eastto Sugar Mill Oils

GRADE: 40, 80 & 120

INTRODUCTION :

These are bituminous lubricants containing non-toxic EP additives and selected compounding agents for efficient lubrication with excellent load carrying ability. These oils prevent wear and corrosion of bearings and also have excellent resistance to leakage.

APPLICATION : Recommended for lubrication of heavily loaded Mill Roll Bearings in Sugar Mills and in centralized lubrication systems of slow speed spur and helical gears in certain Industries and also for open gear lubrication systems.

PERFORMANCE LEVEL :

TYPICAL PROPERTIES:

EASTTO SUGAR MILL OILS			
CHARACTERISTICS	40	80	120
Kinematic Viscosity @ 40°C, cSt.	35 to 45	75 to 90	110 to 130
Flash Point, (COC) °C, Min.	230	230	230
Copper Strip Corrosion @ 100°C., 3 hrs.	1a	1a	1a
Timken OK Load, lbs	35	35	35

PACKING : 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Sugar Mill Oils



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

