

PRODUCT DATA SHEET

PRODUCT: EASTTO EP GREASES

GRADES: NLGI 0, 1, 2, 3

INTRODUCTION: EASTTO EP GREASES 0, 1, 2, 3 are premium quality lithium based extreme pressure greases manufactured from high quality base oils and fortified with specially selected extreme pressure additives for higher load carrying ability. They have excellent Structural stability, Water resistance property, higher drop point, outstanding rust preventive ability and very good oxidation stability.

APPLICATION: EASTTO EP GREASES 0, 1, 2, 3 are recommended for all types of Industrial applications for Plain, Roller and Antifriction Bearings in wide variety equipments operating under severe shock loading conditions, such as Earth moving equipment, Gear couplings, Electric motors, Mining equipment etc. at a temperature up to 130°C.



PERFORMANCE LEVEL: EASTTO EP GREASES 0, 1, 2, 3 meet IS 7623: 1993 EP Types [reaffirmed 2006]

TYPICAL PROPERTIES:

TYPICAL PROPERTIES	EASTTO EP GREASES			
	NLGI 0	NLGI 1	NLGI 2	NLGI 3
Type of Soap	Lithium	Lithium	Lithium	Lithium
Colour	Dark Brown	Dark Brown	Dark Brown	Dark Brown
Worked Penetration @ 25°C.	370	325	280	240
Drop Point °C, Min.	160	170	180	180

PACKING: 182 kgs. Drums

Date of issue: 01.09.2009

Date of revision: 02.03.2017

1st Revision: 30.05.2019 (CK)

PDS No. 06.10.03

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

