

PRODUCT DATASHEET

PRODUCT: Eastto High Vacuum Grease – III

INTRODUCTION: Eastto High Vacuum Grease - III is stiff non - melting grease. It maintains its consistency over a wide range of temperature, from -20°C to 200°C. Its very low volatility, low vapour pressure of the base materials used, makes it an ideal sealant for high vacuum and high pressure systems. The Grease is not affected by water and chemically resistant also.

APPLICATION: Eastto High Vacuum Grease-III is used in lubricating plug valves, Control systems wherein high vacuum or high pressures are encountered and valves remain operational for a longer period despite high temperature and adverse atmospheric conditions.



High Vacuum Grease-III.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO HIGH VACUUM GREASE - III
Appearance	Translucent
Unworked Penetration @ 25°C	240
Softening Point, °C	> 210
Evaporation loss @ 200 °C after 24 hrs	2% Max

PACKING: 1 kg, 2 kg, 5 kg, 20kg, 50 kg.

Date of issue: 20.12.2014

Date of revision: 02.03.2017

1st Revision: 30.05.2019 (CK)

PDS NO. 06.20.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur

