

PRODUCT DATASHEET

PRODUCT: EASTTO HITEMP GREASE

GRADE HITEMP & HITEMP EXTRA

INTRODUCTION: These are non-soap base smooth structured greases for high temperature operating conditions under severe shock load conditions. These greases are water resistant and are not affected by acids / alkalis. They have high mechanical stability for long life and protection against rust. **EASTTO HITEMP EXTRA** contains molybdenum disulphide for extra loads.

APPLICATION: **EASTTO HITEMP** is recommended for plain bearings, anti – friction bearings operating at high temperature (120°C to 250°C). **EASTTO HITEMP EXTRA** is recommended for highly loaded machinery operating at above high temperatures



TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO HIGH TEMP GREASE	
	HITEMP	HITEMP EXTRA
Appearance	Brown	Greenish Black
Worked Penetration at 25°C.	265 to 295	265 to 295
Drop Point °C, Min.	Above 280	Above 280
Copper Corrosion Test at 100°C for 3 hours	Passes	Passes

PACKING: 1 kg, 2 kg, 5 kg, 20kg, 50 kg.

Date of issue: 20.12.2014

Date of revision: 02.03.2017

1st Revision: 30.05.2019 (CK)

PDS NO. 06.20.03

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur

