

## Product Data Sheet

**PRODUCT:** EASTTO HYDRAULIC OILS R & O

**GRADE:** VG 32, 46, 57, 68, 81, 100, 150

**INTRODUCTION:** EASTTO HYDRAULIC OILS R & O are specially developed for circulating and hydraulic transmission system, and are manufactured from highly refined base stocks with high viscosity index. These oils are fortified with anti-oxidant, anti-corrosion, anti-wear, anti-rust and anti-foam additives.

**APPLICATION:** EASTTO HYDRAULIC OILS R & O are suggested for moderate hydraulic systems and wide variety of circulating systems of industrial equipments.



**PERFORMANCE LEVEL:** Meets IS: 3098:1983 [Reaffirmed 2004] Specifications

### TYPICAL PROPERTIES:

EASTTO HYDRAULIC OILS R & O							
Characteristics	32	46	57	68	81	100	150
Kinematic viscosity @ 40°C	32	46	57	68	81	100	150
Viscosity Index	95	95	95	95	95	95	95
Flash Point (COC), °C	190	210	210	210	210	220	220
Pour Point, °C	-6	-6	-6	-6	-6	-6	-6

**PACKING:** 210 Litres Drum

Date of issue : 13.09.2014

Date of Revision: 06.08.2016

1<sup>st</sup> Revision: 29.05.2019 (CK)

PDS No.: 03.02.01 – 03.02.07





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

