

PRODUCT DATASHEET

PRODUCT: EASTTO LOOM OILS N 22, 32, 46, 68, 100, 150, 220, 320, 460

INTRODUCTION: EASTTO LOOM OILS N are highly refined base oils have good inherent oxidation and thermal stability, non-corrosive properties.

APPLICATION: EASTTO LOOM OILS N are generally suggested for non-critical all loss lubrication systems of textile and other looms which do not require additive containing oils. These oils can also be used for other oiling applications of some equipment.



PERFORMANCE LEVEL: IS: 493 (Part 1):1981 [Reaffirmed 2004]

TYPICAL PROPERTIES:

EASTTO LOOM OILS N									
Characteristics	22	32	46	68	100	150	220	320	460
Kinematic viscosity at 40°C	22	32	46	68	100	150	220	320	460
Viscosity Index	90	90	90	90	90	90	90	90	90
Flash Point, COC, °C.	180	190	190	210	220	230	230	240	250
Pour Point, °C.	-6	-6	-6	-6	-6	-6	-6	-3	-3

PACKING: 210 Litres Drum

Date of issue: 10.11.2014

Date of revision: 24.08.2016

1st Revision: 30.05.2019 (CK)

PDS No. 04.03.01 – 04.03.09

These Characteristics are typical of current production while future production will confirm to EASTERN PETROLEUM PVT. LTD. Specification variation in these characteristics may occur.

