

## PRODUCT DATA SHEET

<b>PRODUCT:</b>	<b>EASTTO PROCESS OILS</b>
<b>GRADE:</b>	<b>VG 22, 32, 46, 68, 100, 150, 220, 320, 460</b>
<b>INTRODUCTION:</b>	<b>EASTTO PROCESS OILS</b> are highly refined solvent neutral base oils and have good inherent oxidation and thermal stability, Non-corrosive and excellent ability to separate from water.
<b>APPLICATION:</b>	<b>EASTTO PROCESS OILS</b> are generally suitable for manufacturing of different lubricants, for all lubrication systems and other oiling applications. These oils are also recommended for flushing of inaccessible internal surfaces of various automotive and industrial equipments.



Process oils are highly refined solvent neutral base oils.

<b>PERFORMANCE LEVEL:</b>	IS: 493 (Part 1):1981 [Reaffirmed 2004]
---------------------------	---

### TYPICAL PROPERTIES:

EASTTO PROCESS OILS									
CHARACTERISTICS	22	32	46	68	100	150	220	320	460
Kinematic Viscosity at 40°C	22	32	46	68	100	150	220	320	460
Viscosity Index	95	95	95	95	95	95	95	95	95
Flash Point (COC) °C	170	190	200	210	220	220	225	235	250
Pour Point, °C	-6	-6	-6	-6	-6	-6	-6	-6	-3

**PACKING:** 210 Litres Drum

**Date of issue :** 14.09.2014

**Date of Revision:** 08.08.2016

**PDS No.** 20800 – 20808

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

