

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO CIRCULATING OILS

**GRADE:** VG 22, 32, 46, 68, 100, 150, 220, 320, 460

**INTRODUCTION:** EASTTO CIRCULATING OILS are specially developed for circulating and hydraulic transmission system. They are manufactured from highly refined base stocks and Anti-oxidant, Anti-corrosion, Anti-wear and Anti-foam additives.

**APPLICATION:** EASTTO CIRCULATING OILS are suggested for moderate hydraulic systems and wide variety of circulating systems of industrial equipments. These oils are also recommended for Splash, Bath and ring oiling systems of the bearings (both plain and anti-friction) and gears of industrial machinery that require a long life lubricant. These oils can be used for chain drives and compressor crankcase lubrication.



Moderate hydraulic and compressor systems.

**PERFORMANCE LEVEL:** IS: 3098:1983 [Reaffirmed 2004]

### TYPICAL PROPERTIES:

EASTTO CIRCULATING OILS									
Characteristics	22	32	46	68	100	150	220	320	460
Kinematic viscosity @ 40°C	22	32	46	68	100	150	220	320	460
Viscosity Index, Min.	95	98	95	95	95	95	95	95	95
Flash Point, COC, °C. Min	160	190	210	210	210	220	220	230	230
Pour Point, °C. Min.	-6	-6	-6	-6	-6	-6	-6	-6	-6

**PACKING:** 210 Litres Drum

**Date of issue** : 13.09.2014

**Date of Revision:** 05.08.2016

**PDS No.** 20350 – 20358

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

