Eastto Ban 325

INTRODUCTION: EASTTO BAN 325 is a non-solvent type oily film forming type rust preventive with relatively lower viscosity. **EASTTO BAN 325** is blended from superior base stocks and specially selected additives to provide excellent protection of metal components against rusting for longer duration in indoor and short term in outdoor applications. Because of its non-drying type, the removal of **EASTTO BAN 325** is easier by the treatment with petroleum solvent, alkaline cleaning or vapour degreasing agents. **EASTTO BAN 325** does not require any special precautions during storage, handling and applications as it is free from any solvent.

APPLICATION: **EASTTO BAN 325** can be applied by immersion, brush, swab or spray for protecting iron components from rusting when an oily type rust preventive oil is required by the industries, particularly when the removal of protective oil film is not necessary for subsequent processing of the metallic components e.g. machined parts, nut bolts, metal sheets, nails, steel tube pipes etc

PERFORMANCE LEVEL: EASTTO BAN 325 is a proprietary product.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO BAN 325
Kinematic Viscosity at 40°C., cSt	24
Film Thickness, Micron, Min.	5
Copper Strip Corrosion Test at 100°C for 3 Hrs.	1

PACKING: 210 Litres Drums









Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





an ISO 9001-2008 certified company



EasttoBan 325