

## Eastto Automatic transmission fluid

### GRADE:

TYPE A SUFFIX A OF DEXTRON 1 AND 1B OF GENERAL MOTORS, USA

### INTRODUCTION:

**Eastto** AUTOMATIC TRANSMISSION FLUID A is a premium quality red coloured transmission fluid with low co-efficient of friction to meet Type A Suffix A specification of General Motor. **EASTTO AUTOMATIC TRANSMISSION FLUID A** is blended with highly refined base stock fortified with carefully selected additives to impart good resistance to thermal oxidation, very low temperature flow characteristics, and excellent seal compatibility with anti-wear and anti-corrosion properties. This high viscosity index oil ensures smooth powershift operation with minimum power loss

### APPLICATION:

**EASTTO AUTOMATIC TRANSMISSION FLUID A** recommended for use in both passenger cars and light trucks requiring Type A Suffix A fluid for Automatic Transmission and Power Steering Systems and Syncromesh Gear System.

### PERFORMANCE LEVEL:

Meets the performance level of A SUFFIX A OF DEXTRON 1 AND 1B OF GENERAL MOTORS, USA

### TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO AUTOMATIC TRANSMISSION
Kinematic Viscosity at 40°C., cSt,	7.2
Flash Point, COC, °C. Min.	150
Sulphated Ash, % by Weight, Max	180
Pour Point, °C. Max.	(-)39

**PACKING:** 210 Litres Drum



### Eastern Petroleum Private Limited

Regd. Off.:  
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



## Eastto Automatic transmission fluid