

Product Data Sheet

PRODUCT:
GRADE:
4T 20W-40, 4T 20W-50
INTRODUCTION:

EASTTO SUPREME 4T 20W- 40, 4T 20W-50 are high performance multigrade 4 Stroke Engine oils that are blended from highly refined base stocks and specially selected additives to meet the high temperature operating conditions in air cooled 4 Stroke two wheelers with excellent oxidation stability and, control the sludge and varnish formations. These 4 Stroke Engine oils also provide protection against wear, long engine life, higher fuel efficiency and outstanding engine cleanliness.

APPLICATION:

EASTTO SUPREME 4T 20W- 40, 4T 20W-50 are recommended as multipurpose engine oils for the lubrication of 4 Stroke two wheelers of all models of Motor Cycles, Scooters and Auto rickshaws operating on Petrol and CNG / LPG.



Lubrication of 4 Stroke two wheelers of all models of Motor Cycles, Scooters.

PERFORMANCE LEVEL: Meet the performance level of API SL / JASO T 903 (MA2 Specification).

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SUPREME 4T 20W- 40	EASTTO SUPREME 4T 20W-50
Kinematic Viscosity at 100°C., cSt,	15	17
Flash Point, COC, °C, Min.	200	200
TBN, mg KOH / gm	6.0	6.0
Pour Point, °C, Max.	(-) 21	(-) 21

PACKING: 210 Litres Drum, 50 Litres, 20 Litres, 5 Litres, 1 Litre

Date of issue: 08.09.2014

PDS: 01.18.01 – 01.18.02

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

