

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:

EASTTO GEAR OIL EP 80W, EP 80W-90

INTRODUCTION:

EASTTO GEAR OIL EP 80W, EP 80W-90 are extreme pressure multi grade automotive gear lubricants. These oils are blended from specially selected base stocks and additives to provide extreme pressure, anti-rust, anti-corrosion characteristics.

APPLICATION:

EASTO GEAR OIL EP 80W, EP 80W-90 oils are recommended for passenger car, bus and highway truck for the lubrication of hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.







Spiral bevel Hypoid Gear Worm gear

PERFORMANCE LEVEL:

EASTTO GEAR OIL EP 80W & EP 80W-90 meet the performance level of API service classification GL-4, IS: 1118-1992 EP Type GL-4.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO GEAR OIL EP 80W	EASTTO GEAR OIL EP 80W-90
Kinematic Viscosity at 100°C, cst	9	14.5
Viscosity Index, Min.	90	90
Flash Point, COC, °C.	170	180
Pour Point, °C.	- 24	- 24

PACKING: 210 Litres Drums

Date of issue: 09.09.2014

Date of revision: 26.08.2016

1st Revision: 30.05.2019 (CK)

PDS No. 01.30.03 - 01.30.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

