

Eastern Petroleum Pvt. Ltd. an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990 Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO GEAR OIL EP 90, 140	
INTRODUCTION:	EASTTO GEAR OIL EP 90, 140 are extreme pressure automotive gear lubricants. These oils are blended from specially selected base stocks and additives to provide extreme pressure, anti-rust, anti-corrosion characteristics.	
APPLICATION:	EASTTO GEAR OIL EP 90, 140 oils are recommended for passenger car, bus and highw ay truck for the lubrication of hypoid, spiral bevel and w orm gear axles and also manual transmission for w hich an extreme pressure gear lubricant of this type is required.	
Hypoid gear	Spiral Bevel	Worm gear
	EASTTO GEAD OIL ED 00 ED 140 mosts the performance level of A Plearvice	

PERFORMANCE LEVEL:	EASTTO GEAR OIL EP 90, EP 140 meets the performance level of API service	
	classification GL-4, IS: 1118-1992 EP Type GL-4.	

TYPICAL PROPERTIES	EASTTO GEAR OIL EP 90	EASTTO GEAR OIL EP 140
Kinematic Viscosity at 100°C, cst	17	30
Viscosity Index	90	90
Flash Point, COC, °C.	190	200
Pour Point, °C.	- 9	- 9

PACKING: 210 Liters Drum

Date of issue: 09.09.2014

Date of revision: 26.08.2016

PDS No. 01.30.01 - 01.30.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

