

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO GEAR OIL EXTRA EP 80W-90 GL-5, 85W-140 GL-5
Product Use	:	Automotive Gear oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jaw ahar industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt
	Mineral base oil Multifunctional additi∨e	64742-65-0 Mixture	96 - 98 2 - 4
3.	Hazards identification	Non dangerous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	Not expected to cause Eyes irritation	
	Skin	Not expected to cause skin irritation	
	Inhalation	Not expected to cause any side effect while inhalation	1

4. First Aid Measures

Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flam m ability of product	Combustible liquid
Extinguishing Media	
Suitable	Use dry chemical, carbon dioxide (CO_2), or foam
Not suitable	Do not use water.

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Pick up free liquid for recycling or disposal. The residual oil can be transferred to another container.
Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.

EASTTO GEAR OIL EXTRA EP 80W-90 GL-5, 85W-140 GL-5 Revision No. 3 Date of issue: 04.09.2014 Date of revision: 26.08.2016



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

7.	Handling and Storage		
	Handling	Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment,	
	Storage	vapours or mists might be released and require a well ventilated workplace. Store at ambient temperature or with low est necessary heating as required for ease of handling.	
8.	Exposure Controls / Personal Protection		
	Control parameters	Exposure via air and normal handling	
·	Personal protection equipment		

Respiratory protectionAvoid inhalation use suitable mask with filter if necessary.Hand protectionWear oil-resistant protective gloves if there is a risk of skin contact.Eye protectionFor eyes protection w ear safety goggles.Skin and body protectionUse protective cloths and gloves.Hygienic measuresAct in accordance with good industrial Hygiene and safety practice.

9. Physical and Chemical Properties

CHARCTERISTICS	80W90	85W140
Physical state	Liquid	Liquid
Odour	Mild	Mild
Kinematic viscosity @ 100 °C, cst	14	26
Colour	Brow n	Brow n
Solubility in water	Insoluble	Insoluble
рН	N.A	N.A
Flash point °C	180	200

10. Stability and Reactivity

		Stable at normal conditions and decompose at higher temperature. Excessive heating and highly oxidizing agents ts Hazardous decomposition products are not expected to form during normal storage.
	Hazardous polymerization	Polymerization will not occur.
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No know n significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment

13. Disposal considerations

	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.
14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

16. **Other Information**

The information provided in this Safety Data Sheet is correct to the best of our know ledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a w arranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.