

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:

EASTTO SUPREME 4T 20W- 40, 4T 20W-50

INTRODUCTION:

EASTTO SUPREME 4T 20W- 40, 4T 20W-50 are high performance multi grade 4 Stroke Engine oils that are blended from highly refined base stocks and specially selected additives to meet the high temperature operating conditions in air cooled 4 Stroke two wheelers with excellent oxidation stability and, control the sludge and varnish formations. These 4 Stroke Engine oils also provide antiwear, longer engine life, higher fuel efficiency and outstanding engine cleanness.

APPLICATION: EASTTO SUPREME 4T 20W- 40, 4T 20W-50 are recommended as multipurpose engine oils for the lubrication of 4 Stroke, two wheelers of all models of Motor Cycles, Scooters and Auto rickshaws operating on Petrol and

CNG.





Lubrication of 4 Stroke of all models of Motor Cycles, Scooters and auto rickshaws

PERFORMANCE LEVEL: Meet the performance level of API SL / JASO T 903 (MA2 Specification).

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SUPREME 4T 20W- 40	EASTTO SUPREME 4T 20W-50
Kinematic Viscosity at 100°C,cst	15	17
Flash Point, COC,°C, Min.	200	200
TBN, mg KOH / gm	6.0	6.0
Pour Point, °C	-21	-21

PACKING: 210 Litres Drum, 50 Litres, 20 Litres, 5 Litres, 1 Litre

Date of issue: 08.09.2014

Date of revision: 26.08.2016

PDS: 01.18.01 - 01.18.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

