**Eastto** Base Oil

Eastto Base oil BX-12, BX-32, BX-100 and BX-120

INTRODUCTION: These are highly refined base STOCKS available in Various Viscosity Range. These Oils are having excellent Chemical & Thermal Stability and having High Viscosity Index.

APPLICATION: Bx-12: This Oil is used for manufacture Soluble & Neat Cutting Oils, Textile Lubricants such as Conning Oil, Antistatic Oil, Spin Finish Oil, Shoe Polish, Pigments, Transformer oils, Heat transfer oil, Metal working fluid, Rust preventive oils, Wire drawing oils, Agricultural Spray Oil, Mould Oil, White & Paraffin Oils etc

Bx-32: Recommended for use in Manufacture of Automotive & Industrial Lubricants, Rust Preventives, Flushing Oil, Heat Transfer Oil, White & Paraffin Oil, Metal Finishing Compound, Transformer oil, Specialty lubricants Plasticizer, Rubber Products, Paints, Mould oils etc.

Bx-100 / Bx-120: Recommended for us in Manufacture of Automotive and Industrial Oil, Greases, Pigments, Printing Ink and paints.

PERFORMANCE LEVEL:

## TYPICAL PROPERTIES

EASTTO BASE OIL				
CHARACTERISTICS	Bx-12	Bx-32	Bx-100	Bx-120
Appearance	Clear	Clear	Clear	Clear
Flash Point <sup>o</sup> C, Min (COC)	160	190	210	220
Viscosity Index, Min.	90	95	90	90
Kinematic Viscosity @ 40°C, cSt	12 - 16	27 - 33	88 - 100	115 - 125
Pour Point °C, min	-6	-6	-6	-6
ASTM Colour, Max.	2.5	2.5	3.0	4.0
Inorganic Acidity, Max.	NIL	NIL	NIL	NIL

**PACKING: 210 Litres Drums** 









## **Eastern Petroleum Private Limited**

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





an ISO 9001-2008 certified company



**Eastto**Base Oil, BX-12, BX-32, BX-100/120