Eastto EASTTO PET 30 - Calcium Petroleum Sulphonate

INTRODUCTION: It is manufactured from Sulphonic acid, produced from synthetic base stock, acting calcium as soap.

APPLICATION: It is used in Manufacture of Greases, Rust Preventive Compounds in gasoline and Diesel Engine oils to control piston deposits and Hydraulic oils as detergent additive. It is used in formulation of Metal Working fluids- Rust preventives giving high resistance to humidity and Salt Water Spray Test. It is also used for protective coatings, corrosion inhibitors, lubricants, Lube oil additive, emulsifies in Pesticide, Wetting of solids etc.

PERFORMANCE LEVEL:

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO PET 30
Appearance	Dark Brown Viscous Liquid
Active Matter (as Calcium Sulphonate, Wt. %)	40 – 45
Mineral Oil Content, Wt. %	60.0
K. Viscosity @ 100° C, cSt	222
Calcium Content, Wt. %	2.74
TBN, mg KOH/gm.	28.0
Flash Point, COC,° C Min.	140

PACKING: 210 Litres Drums









Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





Eastern Petroleum Private Limited

an ISO 9001-2008 certified company







EasttoEASTTO PET 30
Calcium Petroleum Sulphonate