Eastto White Mineral Oil LX-100

INTRODUCTION: It is a purified mixture of Liquid Saturated Hydrocarbons, obtained from Petroleum & are highly paraffinic in nature. It is Transparent, Colourless, and Tasteless & Odourless when cold. These highly refined hydro-treated oils, though less refined than their pharmaceutical counterparts have excellent thermal & chemical stability having high flash points & can be used for general industrial applications.

APPLICATION: It is used in the manufacture of Bulk Drugs, Cosmetics, Textile Auxiliaries, Pharmaceutical products, Agrochemicals, Aerosols, Insecticides Oils, Leather Process Oils, Dye Intermediates, Printing inks, Personal care product, Polishes, Paper Industry, Inks, Perfumery, Agarbatti industry, Industrial and automotive Lubricants, Metal working fluid, Polymers, Lubricants additives, Master-batches, Plastics - used as a Lubricant Plasticizers, Extender, Softener during processing of Plastics, Mould release agents etc.

TYPICAL PROPERTIES

EASTTO WHITE MINERAL OIL	
CHARACTERISTICS	LX-100
Appearance	Water White
K. Viscosity @ 40°c, Cst.	95.2
K. Viscosity @ 100°c	10.78
Viscosity Index	97
Density at 29.5°c	0.881
Copper Strip Corrosion	1A
Flash Point Min °c	240
Aniline Point	101
IBP	140
FBP	200

PACKING: 210 Litres M.S. Barrels / Tanker Loads



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





Eastto White Mineral Oil LX-100

