Eastto Pneumatic Tool Oils

GRADE: 46, 100, 181 & 220

INTRODUCTION:

EASTTO PNEUMATIC TOOL OILS are specially developed products blended from highly refined base stocks and selected additives that provide excellent rust preventive and extreme pressure properties with good adhesiveness. These oils have good protection against wear and metal wetting properties that maintain continuous oil film resulting in long equipment life.

APPLICATION: EASTTO PNEUMATIC TOOL OILS are recommended for use in all pneumatically operated rock drills in both underground and surface mining, wagon drills, chippers and jack hammers in building and highway constructions as well as other industrial applications.

PERFORMANCE LEVEL: Proprietary

TYPICAL PROPERTIES:

EASTTO PNEUMATIC TOOL OILS				
CHARACTERISTICS	46	100	181	220
Kinematic Viscosity @ 40°C, cSt.	44 to 48	95 to 105	175 to 185	210 to 230
Viscosity Index	90	90	90	90
Flash Point,°C (COC), Min.	200	200	210	220
Pour Point, °C, Max.	-3	-3	-3	-3

PACKING: 210 Litres Drum









Eastern Petroleum Private Limited

Pord Off

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990

Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





an ISO 9001-2008 certified company





EasttoPneumatic Tool Oils