

Eastto Tool Way Oils

GRADES: VG 32, 68, 100 & 220

INTRODUCTION:

Eastto Tool Way Oils 32, 68, 100 & 220 are blended from highly refined base stocks with excellent oxidation stability and are incorporated with oiliness, anti-wear, non-drip and anti-foam additives. The above combination enables the products to carry higher load of machine tools with minimum stick-slip, chatter and improved surface finish to the job. These grades also protect the parts against rust and corrosion with reduction in the consumption of oils.

APPLICATION:

EASTTO TOOL WAY OILS 32, 68, 100 & 220 are recommended for slide way lubrication of planers, grinders, and shapers by horizontal and vertical guide ways.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO TOOL WAY OILS			
	32	68	100	220
Kinematic Viscosity at 40°C, cSt	30 to 34	64 to 72	95 to 105	210 to 230
Viscosity Index	90	90	90	90
Flash Point, COC, °C, Min.	190	190	210	220
Pour Point, °C. Max.	-3	-3	-3	-3

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Tool Way Oils



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

