

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

# **MATERIAL SAFETY DATA SHEET**

### 1. Product name and Company identification

Product Name	:	EASTTO METAL HONE TX
Product Use	:	Industrial Neat cutting oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar Industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

# 2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt
	Mineral base oil Proprietary additives	64742-65-0 Mixture	80 - 90 5 - 10
3.	Hazards identification	Non dangerous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	Not expected to cause irritation	
	Skin	May cause mild skin irritation if prolonged used	l.
	Inhalation	Not expected to cause any side effect while inh	alation
4.	First Aid Measures		
	Inhalation	If inhaled, remove to fresh air. Get medical atte	ention if symptoms occur.

Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

## 5. Fire-fighting Measures

Flammability of product	Combustible liquid
Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide ( $CO_2$ ), or foam Do not use water.

### 6. Accidental Release Measures

Clean up method- small spillage	environmental pollution (sewers, waterways, soil or air). Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly
Clean up method- small spillage	
-	drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Environmental precautions	as soon as possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways,
Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes

EASTTO METALHONE TX Revision No. 3



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

	Clean up methods – large spillage	Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.	
7.	Handling and Storage		
	Handling	Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace.	
	Storage	Store at ambient temperature or with lowest necessary heating as required for ease of handling.	
8.	Exposure Controls / Personal Protection		
	Control parameters	Use under well ventilated areas	
	Personal protection equipment		
	Respiratory protection Hand protection Eye protection Skin and body protection Hygienic measures	Avoid inhalation use suitable mask with filter if necessary. Wear oil-resistant protective gloves if there is a risk of skin contact. For eyes protection wear safety goggles. Use protective cloths and gloves. Act in accordance with good industrial Hygiene and safety practice.	

#### 9. **Physical and Chemical Properties**

CHARCTERISTICS	EASTTO METAL HONE TX
Physical state	Liquid
Odour	Mild
Colour	Yellow
Sp. Gravity @ 30 °C, gm/ml	0.83
Kinematic viscosity @ 40 °C, cst	5
Solubility in water	Insoluble
рН	N.A
Flash point <sup>0</sup> C	130

#### 10. **Stability and Reactivity**

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decompose at higher temperature. Excessive heating and highly oxidizing agents Upon Combustion, CO <sub>2</sub> , CO and oxides of Sulphur and Nitrogen are generated. Under normal conditions of storage and use, polymerization will not occur.
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment
13.	Disposal considerations	
	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local

environment and health authorities to get the permission for waste disposal.



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information	Not classified as hazardous
16.	Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.