

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in
CIN NO: U24100MH1964PTC012931

## **PRODUCT DATA SHEET**

PRODUCT:	EASTTO PNEUMATIC TOOL OILS 46, 100, 181, 220		
GRADES:			
INTRODUCTION:	<b>EASTTO PNEUMATIC TOOL OILS</b> are specially developed products blended from highly refined base stocks and selected additives that provide excellent rust preventive and extreme pressure properties with good adhesiveness. These oils have good protection against wear and metal wetting properties that maintain continuous oil film resulting in long equipment life.		
APPLICATION:	EASTTO PNEUMATIC TOOL OILS are recommended for use in all pneumatically operated rock drills in both underground and Surface mining, Wagon drills, Chippers and jack hammers in building and highway constructions as well as other industrial applications.		







PERFORMANCE LEVEL: Proprietary product

## **TYPICAL PROPERTIES:**

EASTTO PNEUMATIC TOOL OILS					
CHARACTERISTICS	46	100	181	220	
Kinematic Viscosity @ 40°C, cst.	46	100	180	220	
Viscosity Index	95	95	95	95	
Flash Point (COC) °C	200	220	225	235	
Pour Point, °C	-6	-6	-6	-6	

PACKING: 210 Litres Drum

Date of issue : 20.10.2014

Date of Revision: 08.08.2016

1st Revision: 29.05.2019 (CK)

PDS No. 03.11.01 - 03.11.04





## Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895 Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to EASTERN PETROLEUM PVT. LTD. Specification variation in these characteristics may occur.

