

## Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895 Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

## **PRODUCT DATA SHEET**

PRODUCT:	EASTTO RUBBER EXTENDER OILS		
GRADE	Light, Medium, Heavy, Extra Heavy		
DESCRIPTION:	<b>EASTTO RUBBER EXTENDER OILS Light, Medium, Heavy and Extra heavy</b> are high aromatic type oils and produced during the solvent extraction for the production of lubricating base oils at the Refinery. These are dark coloured oils and have good solvency for which they are compatible with most of the rubber polymers.		
APPLICATION:	<b>EASTTO RUBBER EXTENDER OILS Light, Medium, Heavy and Extra heavy</b> are used in the manufacture of automobile tyres, thread rubber, belting, battery cases, rubber bushes and other dark coloured rubber goods etc. where colour is not an important factor		



Natural and synthetic rubber, Particularly for the manufacturing of automotive rubber tubes

## **TYPICAL PROPERTIES:**

CHARACTERISTICS	EASTTO RUBBER EXTENDER OIL LIGHT	EASTTO RUBBER EXTENDER OIL MEDIUM	EASTTO RUBBER EXTENDER OIL HEAVY	EASTTO RUBBER EXTENDER OIL EXTRA HEAVY
Kinematic Viscosity at 100°C, cst	18 - 21	21 - 26	26 - 30	30 - 40
Flash Point °C	220	220	220	220
Aniline Point, °C	52	50	48	45

PACKING:210 Litres Drum

Date of issue: 05.10.2009

Date of revision: 01.03.2017

1<sup>st</sup> Revision: 29.05.2019 (CK)

PDS No. 07.05.05 - 07.05.08

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

