

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO SUGAR MILL OILS

**GRADES:** 40, 80, 120

**INTRODUCTION:** These are bituminous lubricants containing EP additives and selected compounding agents for efficient lubrication with excellent load carrying ability. These oils prevent wear and corrosion of bearings and also have excellent resistance to leakage.

**APPLICATION:** Recommended for lubrication of heavy loaded Mill Roll Bearings in Sugar Mills and in centralized lubrication systems of slow speed Spur, Helical gears and also for open gear lubrication systems.



Spur Gear



Helical Gears



Roll Bearing

**PERFORMANCE LEVEL:** Proprietary product

### TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SUGAR MILL OILS		
	40	80	120
Kinematic Viscosity at 100°C, cst	40	80	120
Flash Point (COC) °C	230	230	230
Copper Strip Corrosion @ 100°C for 3 hrs.	1a	1a	1a
Timken OK Load, lbs	35	35	35

**PACKING:** 180 Kg Drums

**Date of issue :** 14.09.2014

**Date of revision:** 08.08.2016

**1<sup>st</sup> Revision:** 29.05.2019 (CK)

**PDS No.** 03.45.01 – 03.45.03





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: [office@easternpetroleum.in](mailto:office@easternpetroleum.in), Web: [www.easternpetroleum.in](http://www.easternpetroleum.in)

CIN NO: U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

