

PRODUCT DATA SHEET

PRODUCT: EASTTO MIST OILS

GRADE: VG 32, 46, 68, 100

INTRODUCTION: EASTTO MIST OILS, 32, 46, 68, 100 have been formulated from high quality solvent refined base stocks and a specially selected additive system particularly for optimum reclassifying or agglomerating properties. They have high resistance to oxidation, good extreme pressure, anti-rust and anti-wear properties with enhanced surface wetting capabilities.

APPLICATION: EASTTO MIST OILS are suggested for the oil-fog or mist-lubrication of machine components such as Slide ways, Slow-speed and industrial gearing such as Cooling tower, Gearboxes, High-speed bearings, Chain, and Machine tools.



Gearboxes



Chain



High-speed bearings

PERFORMANCE LEVEL: Proprietary

TYPICAL PROPERTIES:

Characteristics	EASTTO MIST OILS			
	32	46	68	100
VG Grades	32	46	68	100
Kinematic Viscosity at 40°C, cst	32	46	68	100
Viscosity Index	95	95	95	95
Flash Point (COC) °C	200	200	210	220
Pour Point, °C	-6	-6	-6	-6

PACKING: 210 Litres Drum

Date of issue : 14.09.2014

Date of Revision: 08.08.2016

PDS No. 03.12.01 – 03.12.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

