

PRODUCT DATA SHEET

PRODUCT: EASTTO TOOL WAY OILS

GRADES: VG 32, 68, 100, 220

INTRODUCTION: EASTTO TOOL WAY OILS 32, 68, 100, 220 are blended from highly refined base stocks with excellent oxidation stability and are incorporated with oiliness, Anti-wear, Non-drip and Anti-foam additives. The above combination enables the products to carry higher load of machine tools with minimum stick-slip and improved surface finish to the job. These grades also protect the parts against rust and corrosion.

APPLICATION: EASTTO TOOL WAY OILS 32, 68, 100, 220 are recommended for slide way lubrication of Planers, Grinders, and Shapers by horizontal and vertical guide ways. It can be also used in Circulating systems.



Lubrication for sliding

PERFORMANCE: Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO TOOL WAY OILS			
	32	68	100	220
Kinematic Viscosity @ 40°C, cst	32	68	100	220
Viscosity Index	95	95	95	95
Flash Point(COC) °C	190	190	210	220
Pour Point, °C	-6	-6	-6	-6

PACKING: 210 Litres Drum

Date of issue : 14.09.2014

Date of Revision: 08.08.2016

PDS No. 03.10.01 – 03.10.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

