

## PRODUCT DATA SHEET

**BRAND:** EASTTO STEAM CYLINDER OILS

**GRADES:** 680, 1000, 1500

**INTRODUCTION:** These are highly refined steam cylinder oils having excellent chemical and thermal stability and load carrying ability. This oil reduces steam consumption due to good sealing characteristics and minimizes frictional losses.

**APPLICATION:** Recommended as cylinder lubricants for steam engines handling superheated steam. It is recommended where Heavy loads, Slow speeds or High temperatures demands high viscosity lubricants in bearings and enclosed gear sets. It is suitable for worm gear boxes.



Recommended as lubricants for steam engines and cylinder.

**PERFORMANCE LEVEL:** Proprietary product

### TYPICAL PROPERTIES:

TYPICAL PROPERTIES	EASTTO CYLINDER OILS		
	680	1000	1500
Kinematic Viscosity @ 40°C, cst	680	1000	1500
Viscosity Index	85	80	80
Flash Point (COC) °C	280	280	280
Pour Point °C	-3	-3	-3

**PACKING:** 210 Litres Drum

**Date of Issue :** 13.09.2014

**Date of revision:** 08.08.2016

**PDS No.** 20600 - 20602

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

