

PRODUCT DATA SHEET

PRODUCT: EASTTO CONMOL OILS 5, 22

INTRODUCTION: EASTTO CONMOL OILS 5, 22 are high quality mineral oil based mould releasing oils with multi-purpose mould releasing agents for metallic and wooden moulds in concrete construction works. These oils form an excellent oily film on the mould surface that prevents rusting of mould and the release agents prevent concrete clinging to the moulds with a high quality surface finish. These oils do not cause stain or discoloration, interfere with drying process and is also not absorbed by the concrete

APPLICATION: EASTTO CONMOL OILS 5, 22 are recommended to use neat and it can be applied by spraying guns, rollers or by brushes prior to pouring aerated concrete and are recommended for use as a concrete mould release agent with the protection of moulds from rust.



Oils are applied by spraying guns, rollers, moulds, etc.

PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO CONMOL	
	5	22
GRADE	5	22
Kinetic Viscosity at 40°C., cst	5	22
Colour, ASTM, Max.	3.0	3.0
Flash Point, °C, Min.	120	160
Pour Point, °C.	-3	-3

PACKING: 210 Litres Drums

Date of issue: 10.11.2014

Date of revision: 24.08.2016

1st Revision: 30.05.2019 (CK)

PDS No. 07.04.01 – 07.04.02





Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 25299990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**
Specification variation in these characteristics may occur.

