

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. **Product name and Company identification**

Product Name	:	EASTTO BAN 325
Product Use	:	Industrial Rust Preventive Oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar Industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. **Composition / Information of Ingredients**

	Ingredient name	CAS Number	% by wt	
	Mineral base oil Proprietary additives	64742-65-0	85 - 95 5 -15	
3.	Hazards identification	fication Non dangerous substance		
	Physical state	Liquid		
	Human Health Effects			
	Eyes	Not expected to cause irritation		
	Skin	May cause mild skin irritation if prolonged used		
	Inhalation	Not expected to cause any side effect while inhalation		

4. **First Aid Measures**

Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur
Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately Get medical attention if symptoms occur.

5. **Fire-fighting Measures**

Flammability of product	Combustible liquid	
Extinguishing Media		
Suitable	Use dry chemical, carbon dioxide (CO_2) , or foam	
Not suitable	Do not use water.	

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.	
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.	
EASTTO BAN 325 Revision No. 3	Date of issue: 10.11.2014 Date of revision: 12.08.2016	



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

7. Handling and Storage

Handling

Storage

Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. Exposure Controls / Personal Protection

Control parameters

Use under well ventilated areas

Personal protection equipment

Respiratory protectionAvoid inhalation use suitable mask with filter if necessary.Hand protectionWear oil-resistant protective gloves if there is a risk of skin contact.Eye protectionFor eyes protection wear safety goggles.Skin and body protectionUse protective cloths and gloves.Hygienic measuresAct in accordance with good industrial Hygiene and safety practice.

9. Physical and Chemical Properties

CHARCTERISTICS	EASTTO BAN 325
Physical state	Liquid
Odour	Mild
Colour	Dark Brown
Sp. Gravity @ 30 °C, gm/ml	0.88
Solubility in water	Insoluble
pH	N.A
Flash point ^o C	180

10. Stability and Reactivity

	Reactivity and stability Conditions to avoid Hazardous decomposition products Hazardous polymerization	Stable at normal conditions and decomposes at higher temperature. Excessive heating and highly oxidizing agents Upon Combustion, CO_2 , CO and oxides of Sulphur and Nitrogen are generated. polymerization will not occur.
11.	Toxicological Information	
	Potential chronic health effects Carcinogenicity	No known significant effects or critical hazards.
12.	Ecological Information	
	Environment effect:	Will not have chronic effect on aquatic environment
13.	Disposal considerations	
	Waste disposal procedure:	Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations. Contact local environment and health authorities to get the permission for waste disposal.
14.	Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15.	Regulatory Information	Not classified as hazardous.



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

16. Other Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.