

Eastto Knitting Oils

INTRODUCTION : EASTTO LOOM OILS N have good inherent oxidation and thermal stability, non-corrosive with light in colour.

APPLICATION : EASTTO LOOM OILS N are generally suggested for non-critical all loss lubrication systems of textile and other looms which do not require additive containing oils. These oils can also be used for other oiling applications of some equipment.

TYPICAL PROPERTIES

EASTTO LOOM OILS N									
CHARACTERISTICS	22	32	46	68	100	150	220	320	460
KV at 40°C	20 - 24	30 - 34	43 - 49	64 - 72	95 - 105	145 - 155	210 - 230	300 - 340	440 - 480
VI, Min.	90	90	90	90	90	90	90	90	90
Flash Point, COC, °C. Min	160	160	160	160	170	190	200	220	220
Pour Point, °C. Max.	-6	-6	-6	-6	-6	-6	-6	-3	-3

PACKING: 210 Litres M.S. Barrels / Tanker Loads



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Loom Oils N



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

