Eastto Transformer Oil

INTRODUCTION:

Eastto Transformer Oil is having excellent insulating properties, good oxidation stability, low volatility and resistance to sludge formation. The oil is free from acid, alkali and corrosive sulphur and excellent demulsibility characteristic.

APPLICATION: Recommended for use in Capacitors, Circuit Breakers and Transformers.

TYPICAL PROPERTIES:

| Characteristics | Eastto Transformer Oil |
|--|------------------------|
| Density at 29.5⁰C | 0.890 |
| Flash Point, ºC (Pensky – Martin closed) | 140 |
| Pour Point °C | Minus 6 |
| Kinematic Viscosity at 27ºC, cSt | 27 |
| Breakdown Voltage, new unfiltered / after filtration | 30 / 60 |
| Corrosive Sulphur | Non-corrosive |
| Oxidation Stability at 100°C, 164 Hrs. | |
| a) Total Acidity | a) 0.4 |
| b) Sludge | b) 0.1 |
| Water Content, ppm | 50 |
| Presence of Oxidation Inhibitor | Nil |

PACKING: 20,26,210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





Eastto Transformer Oil



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company